

AXLE ORDER FORM - 23,25 & 28 SPLINE

	OFF	JJE
CV	ı.	

MALL BEARING 35.02mm 4140 INDUCTION HARDENED ALLOY AX

	40 INDUCTION HARDENED ALLOY AXLE	IND.				
BILLING ADDRESS	SHIPPING ADDRESS	INV:				
NAME:	NAME:					
ADDRESS:	ADDRESS:					
SUBURB:	SUBURB:					
STATE:	STATE:	TATE:				
POSTCODE:	POSTCODE:	OSTCODE:				
PHONE:	PHONE:					
FAX:						
E-MAIL:						
MEASURING FOR INDIVIDUAL AXLE LENGTHS						
F "PCD"	(42mm) (42mm) (15.02mm) (35.02mm)	n SPLINE				
BRAKE TYPE :	C C					
BEARING END TYPE :		-1				
TYPE OF REAR END :	A : B :					
SPLINE COUNT :	D : E :					
STUD SIZE / TYPE :	F : G :					
HOLE / THREAD SIZE :	STUD PATTERN:					
DRIVERS SIDE DIMENSIONS: MATERIAL 4140	PASSENGERS SIDE DIMENSIONS:	MATERIAL 4140				
C : OFFICE USE	C :	OFFICE USE				
ADDITIONAL INFORMATION:						

STANDARD

- AXLE FLANGES DRILLED WITH 1" HOLE FOR ACCESS TO RETAINER BOLTS
- AXLE FLANGES DIAMETER "G" STANDARD = 150mm
- AXLES DRILLED & TAPPED TO ACCEPT SCREW IN STUDS (HIGHLY RECOMMENDED FOR THIS TYPE OF AXLE)
- 25 SPLINE AXLES HAVE SPLINE WITH 30° PRESSURE ANGLE
- 23 & 28 SPLINE AXLES HAVE SPLINE WITH 45° PRESSURE ANGLE
- ALL SPLINES ARE CUT TYPE
- MATERIAL: 4140 INDUCTION HARDENED USA ALLOY AXLE
- AXLES ARE PACKAGED IN CARDBOARD BOXES FOR SAFE DELIVERY

CONTACT DETAILS

ALTRA 9

UNIT 2 / 143 GRANITE STREET GEEBUNG QLD 4034

PHONE: (07) 3265 5200 (07) 3265 5155 WEB: www.altra9.com.au EMAIL: info@altra9.com.au

- WHEN PLACING AN ORDER YOU AGREE TO OUR TERMS AND CONDITIONS
- TERMS AND CONDITIONS ARE AVAILABLE ON WEBSITE
- FULL PAYMENT IS REQUIRED BEFORE ORDER WILL BE PROCESSED

PAYMENT METHODS

EFTPOS, CREDIT CARD(SURCHARGE), CASH, DIRECT DEPOSIT